

4-10-00

H

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Box PATENT APPLICATION  
 ASSISTANT COMMISSIONER FOR PATENTS  
 Washington, D.C. 20231

Docket No. 1069 1030

Sir:  
 Transmitted herewith for filing is the patent application of

Inventors: Michael D. Mabry and Donald R. McAllister

For: SEALABLE LID FOR VACUUM DISTILLATION APPARATUS

Enclosed are:

- ☒ (12) PAGES OF SPECIFICATION  
☒ (5) PAGES OF CLAIMS  
☒ (1) PAGE OF ABSTRACT  
☒ (3) SHEETS OF DRAWINGS (INFORMAL)  
☒ ASSIGNMENT OF THE INVENTION TO: IHS SOLVENT SOLUTIONS, INC. (COPY)  
☒ (COPY) ASSIGNMENT RECORDATION FORM COVER SHEET  
☒ (COPY) NOTICE OF RECORDATION OF ASSIGNMENT  
☒ (COPY) DOCUMENT REEL/FRAE 01 010259/0256  
☒ DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION  
☒ DECLARATION OF SMALL BUSINESS CONCERN

For:	Number Filed	Number Paid For	Number Extra	Rate	Total
Application				\$690.00/\$345.00	\$345.00
All Claims	20	20	-0-	\$18.00 / \$9.00	-0-
Independent Claims	2	3	-0-	\$78.00 / \$39.00	-0-
Total Filing Fee-----	-----	-----	-----	----->	\$345.00


PLEASE CHARGE MY DEPOSIT ACCOUNT NO. 09-0528 IN THE AMOUNT OF \$ \_\_\_\_\_,  
 A DUPLICATE COPY OF THIS SHEET IS ENCLOSED.

☒ THE COMMISSIONER IS HEREBY AUTHORIZED TO CHARGE ANY ADDITIONAL FEES WHICH  
 MAY BE REQUIRED, OR CREDIT ANY OVERPAYMENT TO DEPOSIT ACCOUNT NO. 09-0528.

\_\_\_ A CHECK IN THE AMOUNT OF \$ 345.00 \_\_\_ IS ATTACHED.

\_\_\_ A CHECK IN THE AMOUNT OF \$40.00 TO COVER THE ASSIGNMENT RECORDING FEES IS  
 ENCLOSED.

WOMBLE CARLYLE SANDRIDGE & RICE, PLLC  
 P.O. Box 725388  
 Atlanta, Georgia 31139-9388  
 (404) 872-7000


  
 Jeffery B. Arnold  
 Registration No. 39,540

Express Mail Certificate

I hereby certify that this correspondence is being deposited with the United States Postal Service as  
 "Express Mail Post Office to Addressee" in an envelope addressed to: Box PATENT APPLICATION, Assistant  
 Commissioner for Patents, Washington, D.C. 20231 on April 7, 2000

Express Mail No. EL551683316US

Signature



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: **Michael D. Mabry and Donald R. McAllister**  
For: **SEALABLE LID FOR VACUUM  
DISTILLATION APPARATUS**

## CERTIFICATE OF EXPRESS MAIL

Assistant Commissioner for Patents  
Box PATENT APPLICATION  
Washington, D.C. 20231

Sir:

Enclosed for filing in the above case are the following documents:

Transmittal  
Specification (12 pages)  
Claims – ( 5 pages)  
Abstract (1 page)  
Drawings – Figs. (3 pages) (Formal)  
Declaration and Power of Attorney  
Small Entity Statement – Independent Inventor  
Small Entity Statement – Claimant  
Filing Fee - \$345.00 – Check# 016879  
Copy of Notice of Recordation of Assignment Document dated 9/24/99, Reel/Frame  
010259/0256 of U.S. Provisional Patent Application Serial No. 60/128,818 filed April 12, 1999  
Copy of Corrective Recordation Cover Sheet dated 12-03-99  
Copy of Assignment dated May 10, 1999  
Return Postcard

~~Respectfully submitted,~~

Jeffery B. Arnold  
Reg# 39,540

P.O. Box 720601  
Atlanta, GA 30358-2601  
404-962-7523

Docket Number: **I069 1030**

I hereby certify that all correspondences listed above are being deposited for delivery to the above addressee, with the United States Postal Service **"EXPRESS MAIL POST OFFICE TO ADDRESSEE"** service under 37 CFR 1.10 on the date indicated below:

The envelope has been given U.S. Postal Service "Express Mail Post Office To Addressee"  
Package #EL551683316US.

April 7, 2000  
Date

NOELIA VARGAS  
(Printed Name of Person Mailing Correspondence)

Isabella Vargas  
(Signature of Person Mailing Correspondence)

Applicant: Michael D. Mabry and Donald R. McAllisterEntitled: SEALABLE LID FOR VACUUM DISTILLATION APPARATUS**VERIFIED STATEMENT (DECLARATION)****CLAIMING SMALL ENTITY STATUS****{37 CFR 1.9(F) AND 1.27 (B)} - INDEPENDENT INVENTOR**

As a below named inventor, I hereby declare that:

I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled **SEALABLE LID FOR VACUUM DISTILLATION APPARATUS**

described in the specification filed herewith.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☐ No such person, concern, or organization  
☒ Persons, concerns or organizations listed below\*

\*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the inventions averring to their status as small entities. (37 CFR 1.27)

Full Name IHS Solvent Solutions, Inc.Address 1520 Airport Drive, Ball Ground, Georgia 30107

☐ Individual ☒ Small Business Concern ☐ Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. {37 CFR 1.28(b)}

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Michael D. Mabry

Name of Inventor

Signature of Inventor

Date Signed

Donald R. McAllister

Name of Inventor

Signature of Inventor

Date Signed

Applicant: Michael D. Mabry and Donald R. McAllisterEntitled: SEALABLE LID FOR VACUUM DISTILLATION APPARATUSVERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY  
STATUS {37 CFR 1.9 AND 1.27} - CLAIMANT OF PATENT RIGHTS

As a below named Claimant, We hereby declare that:

We qualify as ☒ a Small Business Concern ☐ a Non-Profit Organization as defined in 37 CFR 1.9 for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled **SEALABLE LID FOR VACUUM DISTILLATION APPARATUS** described in the specification filed herewith.

We have not assigned, granted, conveyed or licensed and are under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ No such person, concern, or organization  
☐ Persons, concerns or organizations listed below

Full Name \_\_\_\_\_

Address \_\_\_\_\_

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

We acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. {37 CFR 1.28(b)}

I, the undersigned individual, warrant that I am an officer authorized to execute this document on behalf of the Claimant; I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Date: 04/07/00By: Michael D. Mabry

Typed Name: Michael D. Mabry

Position: President

## SEALABLE LID FOR VACUUM DISTILLATION APPARATUS

This application claims benefit of U.S. Provisional Patent Application No. 60/128,818 filed April 12, 1999, which is incorporated herein by reference.

### FIELD OF THE INVENTION

5       The present invention relates generally to the field of manhole covering devices. More particularly, the present invention relates to a device for sealing a manhole of a vacuum still utilized in the recovery of a photopolymer solvent.

### BACKGROUND OF THE INVENTION

10       It is known in the prior art to produce printing plates from acrylic elastomer resins and synthetic rubbers utilizing photoengraving and chemical milling techniques. Generally, a layer of such resins or rubbers are placed onto a surface of a flexible plate and then exposed to light through a photographic film or stencil having a desired pattern to be formed onto the printing plate. Exposure of the resins and rubbers to light cures the resins and rubbers, altering the susceptibility of the  
15       resins and rubbers to removal by a photopolymer solvent. By applying the photopolymer solvent to the light exposed layer of resins or rubbers on the printing plate, the uncured photopolymer resin or rubber is chemically etched away by the photopolymer solvent in a pattern reverse to that of the film or stencil. The resin or rubber etched from the plate is removed with the waste photopolymer fluid.

20       Typically, the solvents utilized for the photopolymer solvent are relatively costly and generally have flash point temperatures above 140° F. Further, disposal

of the waste photopolymer fluid is likewise relatively expensive and presents environmental problems and concerns. Therefore, to more efficiently produce the aforementioned printing plates, devices were developed to recover the photopolymer solvent from the waste photopolymer fluid.

5           Prior art photopolymer solvent recovery apparatus utilize vacuum assisted distillation typically within a still to separate the photopolymer solvent from the photopolymer resins or rubbers. Upon separation and removal of the photopolymer solvent, the residue resins or rubbers remain in the device as a concentrated residue. Typically, the residue is removed from the device by gravity flow through a drain.

10          Due to the relative cost of the photopolymer solvent, the operator desires to maximize solvent recovery, however, the recovery of the photopolymer solvent is limited. Over a period of time, concentrated resins or rubbers can coalesce into an amorphous solid residue and cake onto internal surfaces and parts of the still. Once the solid is formed, the apparatus can not be operated until the operator enters and  
15          manually removes the solid from the device. Further, because the distillation process involves cyclic heating, it is desirable to periodically inspect the internal structure and parts of the distillation device for signs of structural fatigue.

Generally, internal access to the distillation device by the operator is gained through a manhole which utilizes a removable closure.

20           In the photopolymer solvent recovery industry, recent innovations have been primarily directed to maintaining residue fluidity while attempting to maximize photopolymer solvent recovery. However, very little attention has been given to the manhole and closure of the distillation apparatus. Typically, manhole and closure

assemblies consist of a manually adjustable threaded closure which releasably engages mating threads located around the perimeter of a rim extending upwardly proximate the manhole. The fastener assemblies secure the closure on the distillation apparatus and seal the interior thereof. A center speed ball handle lifts the closure from the apparatus, with the fasteners disconnected, and swings away from the open top of the tank on a davit arm. An example of such a manhole and closure assembly is described in U.S. Patent Number 5,308,452 to Marks et al.

In our pending U.S. Patent Application No. 09/151,222 filed September 10, 1998, entitled "Modular Solvent Recovery Device", a manhole device is described which removably covers and seals a manhole of a still which can be quickly and easily engaged by a single operator. The manhole device comprises a pivotally and telescopically mounted closure which removably engages an annular flange extending outwardly from the still at the manhole. Wheels rotatably mounted to the closure engage tracks, which are positioned on the still, to raise the closure vertically above the manhole upon pivotal movement of the closure. The tracks have rounded or tapered shoulders at their proximal ends to immediately engage the wheels upon initiation of pivotal movement of the closure. As the closure pivots by a relatively nominal physical effort by the operator, the wheels engage the respective shoulders and cause the closure to disengage and vertically rise above the flange. As the closure continues to pivot, the wheels roll along the tracks to clear the closure from obstructing the manhole. A stop mounted to at least one of the tracks proximate its distal end engages the closure to terminate pivotal movement beyond the stop. A foam-covered handle extends outwardly from the closure to assist the operator in

pivoting and raising the closure. To assist in sealing the closure to the flange, a gasket is disposed between the closure and the rim. Clamps are pivotally mounted to the still adjacent the flange to releasably engage the closure and contract the closure into sealable engagement with the flange. By pivoting the closure away  
5 from the stop, the wheels roll upon and disengage the respective tracks at the shoulders, thereby permitting the closure to drop and seat on the flange and form a sealable engagement with the manhole upon clamping. Unfortunately, because the gasket must rest upon the flange to form the seal, the gasket is not secure from movement along the flange upon pivotal action of the closure. This can result in a  
10 poor seal and/or a damaged gasket. In an effort to secure the gasket from movement, the closure can be provided with an annular groove disposed adjacent a periphery thereof to receive the gasket. However, the gasket can slip downwardly or even fall from the groove due to gravitational forces, particularly when the gasket is pliant due to heating, and again result in a poor seal and/or damaged gasket. Further,  
15 because the gasket must rest upon the flange, a costly endless annular gasket is generally required to form the seal.

Despite existing manhole and closure assemblies, the need remains for a sealable lid for a vacuum distillation apparatus which secures a gasket from movement and removably covers and seals a manhole of the distillation apparatus or  
20 other vessel which can be quickly and easily released from, moved about, and engaged with the manhole by nominal physical effort of a single operator. Further, there remains a need for such a device which permits utilization of a non-endless gasket. Accordingly, it is to the provision of a sealable lid for a vacuum distillation



apparatus that meets these needs that the present invention is primarily directed.

## SUMMARY OF THE INVENTION

This invention overcomes the disadvantages of the prior art by providing a sealable lid assembly for a manhole of a vacuum distillation apparatus utilized to recover photopolymer solvent. The sealable lid assembly comprises a flange having an exterior surface and an interior surface surrounding the manhole and extending outwardly from the vacuum distillation apparatus to a distal end. A channel is positioned on either the exterior or interior surfaces of the flange proximate the distal end to receive a gasket, such as a TEFLON gasket. Proximate the manhole is a shaft which extends outwardly from the vacuum distillation apparatus. A lid is pivotally and telescopically mounted to the shaft and is capable of releasably and sealably engaging the flange. The lid has a substantially dome-shaped top and a substantially planar bottom, and the top and bottom in combination define a chamber within the lid. Insulation may be disposed within the cavity. A protrusion extends outwardly from a bottom of the lid in a position to extend into the channel and sealably engage the gasket. Spaced-apart wheels are rotatably mounted to the lid. Tracks are disposed on the vacuum distillation apparatus in a position to engage the wheels and raise the lid vertically above a manhole of the vacuum distillation apparatus upon pivotal movement of the lid, which is initiated by nominal physical exertion of a single operator. Clamp assemblies are disposed on the lid and the vacuum distillation apparatus to releasably contract the protrusion into sealable, releasable engagement with the gasket. The gasket can be an endless type or non-endless type with obtuse faces oppositely and matingly positioned adjacent one another in the

channel. A handle extends outwardly from the lid to assist the operator in pivotally moving the lid.

Thus, a unique sealable lid assembly is now provided that successfully addresses the shortcomings of existing manhole closures and provides distinct advantages over such manhole closures. Additional objects, features, and advantages of the invention will become more apparent upon review of the detailed description set forth below when taken in conjunction with the accompanying drawing figures, which are briefly described as follows.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 is a partial perspective view of a sealable lid assembly made in accordance with the present invention disposed on a vacuum distillation apparatus.

Figure 2 is a partial perspective view a manhole on the vacuum distillation apparatus.

Figure 3 is a partial side view of a lid sealably engaging a gasket disposed within a channel of a flange.

Figure 4 is a partial perspective view of the lid with a wheel engaging a track.

Figure 5 is a partial side elevation view of the lid and an engaged J-clamp and the J-clamp released from the vacuum distillation apparatus.

Figure 6 is a partial side elevation view of the lid and and an engaged U-clamp.

Figure 7 is a front elevtion view of the U-clamp of Figure 6.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

For a more complete understanding of the present invention, reference should be made to the following detailed description taken in connection with the accompanying drawings, wherein like reference numerals designate corresponding parts throughout the several figures. Referring first to Figure 1, a sealable lid assembly 46 made in accordance with the present invention is shown mounted to a vacuum distillation apparatus 40 of a solvent recovery device (not shown) which is operably connected in fluid communication with a conventional plate processor (not shown). An example of such a modular solvent recovery device and its operation is discussed in U.S. Patent Application Serial No. 09/151,222, which is incorporated herein in its entirety by reference. The plate making process that takes place in the plate processor is conventional, is not a part of the present invention, and therefore, is not described in detail. The component parts of the device are connected in operative fluid communication with the plate processor through a solvent feed conduit and a waste photopolymer fluid conduit. The solvent feed conduit transports solvent from the device to the plate processor, and the waste photopolymer fluid conduit transports waste photopolymer fluid generated during plate making operations of the plate processor to the device.

Referring additionally to Figures 2 and 3, the vacuum distillation apparatus 40, also known as a still, comprises a sealable pressure vessel having an apparatus interior 41 accessible through an opening 42 located at the top of the apparatus 40. Extending outwardly from the apparatus 40 and surrounding the opening 42 is a annular flange 43 which has an inner surface 16, an outer surface 18, and terminates

at a distal end 12. The flange 43 and the opening 42 in combination define a manhole 10. A generally L-shaped wall 14 extends outwardly and upwardly from the flange 43 proximate the distal end 12. The L-shaped wall 14 and the flange 43 in combination define a channel 44. As shown in Figure 1, the L-shaped wall extends from the inner surface 16, and as shown in Figure 3, the L-shaped wall extends from the outer surface 18.

During operation, the manhole 10 is sealed by a sealable lid 47 made in accordance with the present invention. The lid 47 is pivotally and telescopically mounted to the apparatus 40 adjacent the flange 43. Extending outwardly from the lid 47 is an arm 48 having a mounting cylinder 49 which pivotally and slidably engages a shaft 50 extending outwardly from the apparatus 40. As additionally shown in Figure 4, oppositely and rotatably mounted to the lid 47 are two spaced-apart wheels 51. Two elongated, spaced-apart tracks 52 extend upwardly from the apparatus 40 proximate the flange 43 along the respective paths of the wheels 51 to engage the wheels 51 as the lid 47 pivots away from the manhole 42. At a proximal end 53 of the tracks 52 are rounded shoulders 54 positioned to engage the wheels 51 upon pivotal movement of the lid 47. An elongated ramp 20 extends from the shoulder 54 along an angle of about 30° to about 60°, preferably 45°, with respect to the distal end 12 of the flange 43 to reduce the amount of force needed by the operator to pivot the lid 47. The ramp 20 terminates at an apex 21, which is sufficiently vertically disposed above the apparatus 40 so that the lid 47 pivots freely without striking any obstruction thereon. Alternatively, the ramp 20 can extend from the apparatus 40 to the apex 21 without a shoulder 54 being present. As the lid 47

pivots, the wheels 51 engage the respective shoulders 54 and cause the lid 47 to vertically rise above the flange 43 and roll along the tracks 52 to clear the lid 46 from obstructing the manhole 10. Because the wheels 51 are oppositely disposed on the lid 47, the mounting cylinder 49 slides upwardly along the shaft 50 with minimal binding. At least one stop 55 is optionally mounted to one of the tracks 52 to engage the respective wheel 51 and prevent the lid 47 from pivoting beyond the track 52. If the stop 55 is absent, the shaft 50 should be reinforced to support the weight of the lid 47. A handle 56 extends outwardly from the lid 47 to assist a single operator in pivoting and raising the lid 47. The handle 56 is foamed covered for improved gripping capability by the operator.

Referring again to Figures 1 and 3, the lid 47 has a substantially dome-shaped top 22 and a lid bottom 63, thereby forming a chamber 64. A lip 24 extends beyond the lid bottom 63 which at least partially covers the flange 43 while the lid 47 is engaged therewith. Insulation 65 is disposed within the chamber 64 to retain heat within the apparatus 40. Extending outwardly from the lid bottom 63 is an annular protrusion 66, which inserts into the channel 44 when the lid 47 is disposed over the manhole 42 and the wheels 51 disengage the tracks 52. A gasket 62 is disposed within the channel 44 to assist in sealing the lid 47 to the flange 43. As mentioned above, the protrusion 66 projects into the channel 44 to engage the gasket 62 and form the lid 47/flange 43 seal.

A plurality of clamp assemblies 57 are provided to contract the lid 47 into sealable engagement with the flange 43. As illustrated in Figures 1 and 4, in one embodiment, the clamp assembly 57 comprises receivers 58 having U-shaped slots

59 mounted to the lid 47. Pivotaly mounted to the apparatus 40 are threaded bolts 60 which are removably placeable into the slots 59. Matingly threaded wing nuts 61 are adjustably disposed on the bolts 60. Upon rotation of the nuts 61 in one direction, the nuts 61 respectively engage the receivers 58 and exert pressure against the receivers 58 to seal the lid 47 to the flange 43. That is, the protrusion 66 is drawn into the channel 44 to sealably engage the gasket 64. Rotating the nuts 61 in the opposite direction releases the pressure and enables the bolts 60 to be pivoted and removed from the slots 59 so that the lid 47 may be unseated from the flange 43. As the lid 47 is pivoted in the opposite direction from the stop 55, the wheels 51 rollingly engage the respective tracks 52 and disengage the tracks 52 at the shoulders 54, permitting the lid 47 to seat on the rim 45 of the flange 43 and seal the manhole 42.

Now, referring to Figure 5, the clamp assembly 57 may also comprise a lockable J-clamp 68 mounted to the lid 47. Such J-clamps, generally referred to as latch action clamps, have adjustable hooks 24 to controllably vary the clamping pressure of the clamp and are manufactured by DE-STA-CO Industries, Birmingham, MI, (model numbers 330, 351, 371, and 381). The J-clamps 68, which can have lockable levers, removably engage clamp pins 69, which are mounted to the apparatus 40, to draw the protrusion 66 into sealable engagement with the gasket 62. Upon releasing the respective levers, the J-clamps 68 can be disengaged from the clamp pins 69 to release the lid 47.

As shown in Figures 6 and 7, the clamp assembly 57 can also comprise a U-clamp 80 mounted to the lid 47. Such U-clamps 80, generally referred to as

latch action or pull action clamps, have adjustable U-shaped bars 82 to controllably vary the clamping pressure of the clamp and are manufactured by DE-STA-CO Industries, Birmingham, MI, (model numbers 324, 334, 344, 374, 331-R and 341-R). The U-clamps 80, which can have lockable levers, respectively, removably engage slots 86 of clamp stays 84, which are mounted to the apparatus 40 adjacent the flange 43, to draw the protrusion 66 into sealable engagement with the gasket 62. Upon releasing the respective levers, the U-clamps 80 can be disengaged from the clamp stays 84 to release the lid 47.

Solvents are employed in the plate processor to dissolve portions of a synthetic polymeric resin plate exposed to light in a photopolymer plate making process. The waste photopolymer fluid received by the device from the plate processor contains a mixture of the selected solvent and photopolymer solids consisting of acrylic elastomer resins and synthetic rubber. The photopolymer solids are soluble in the selected solvent.

A heating assembly (not shown) heats the apparatus 40 and the contents of the apparatus interior 41. As the temperature of the oil contained in the jacket is increased by the heater, the apparatus 40 and the material contained in the apparatus interior 41 are heated by conduction.

Vacuum pressure is created in the apparatus 40 by a vacuum pump (not shown) sufficient to draw waste photopolymer into the apparatus 40. A solvent discharge conduit (not shown) communicates with the apparatus interior 41 and extends to the vacuum pump. The vacuum pump provided in the solvent discharge conduit creates a vacuum pressure in the solvent discharge conduit and the apparatus

40. The clamp assemblies should provide sufficient pressure while engaged to seal the lid 47 to the flange 43. The vacuum pressure draws distilled solvent from the apparatus interior 41.

As the apparatus 40 distills the waste photopolymer fluid, solvent is removed from the apparatus 40 and the waste photopolymer fluid is reduced to the concentrated residue, which can coalesce into an amorphous solid residue and cake onto internal surfaces and parts of the apparatus 30. The desired solvent to be distilled may be any number of commercially available solvent blends, including the widely used prior art solvent blend of alcohol-perchloroethylene. Examples of some commercial solvents typically employed in plate making operations by plate processors to dissolve portions of the photopolymer coated plate include solvents marketed under the tradenames OPTISOL, distributed by DuPont Company; SOLVIT, distributed by Polyfibron Technologies, Inc.; and NUTRE CLEAN, distributed by NuPro Technologies. The gasket 62 should be made from a material which is inert to and non-soluble in the photopolymer solvent, particularly at elevated temperatures above ambient. Preferably, the gasket at least has a coating made of tetrafluoroethylene fluorocarbon polymers, fluorinated ethylene-propylene resin, or a mixture thereof, which are marketed under the tradename TEFLON. Typically, such TEFLON coated gaskets have a silicone rubber core. Optionally, the gasket 62 may comprise a braid of fibers or strands made from tetrafluoroethylene fluorocarbon polymers, fluorinated ethylene-propylene resin, or a mixture thereof.

Referring again to Figure 2, the gasket 62 can be an endless, annular gasket



or can be an elongated strip having two ends 67. The ends 67 have faces (not shown) disposed at obtuse angles with respect to the elongated portion of the gasket 62 so that the faces oppose one another when the gasket is placed in the channel 44.

With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of the invention, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by the present invention. Further, the various components of the embodiments of the invention may be interchanged to produce further embodiments and are these further embodiments are intended to be encompassed by the present invention.

Therefore, the foregoing is considered as illustrative only of the principles of the invention. Further, various modifications may be made of the invention without departing from the scope thereof and it is desired, therefore, that only such limitations shall be placed thereon as are imposed by the prior art and which are set forth in the appended claims.

## WHAT IS CLAIMED IS:

1. A sealable lid assembly for a manhole of a vacuum distillation apparatus utilized to recover photopolymer solvent, comprising:
  - a flange surrounding the manhole and extending outwardly from the vessel to a distal end;
  - 5 at least one wall extending from the flange proximate the distal end to define a channel;
  - a shaft extending outwardly from the vessel proximate the manhole;
  - a lid pivotally and telescopically mounted to the shaft capable of releasably and sealably engaging the flange;
  - 10 a protrusion extending outwardly from the lid and insertable into the channel;
  - at least one wheel rotatably mounted to the lid;
  - at least one elongated track extending outwardly from the vessel in a position to engage the at least one wheel and raise the lid vertically above the flange as the lid
  - 15 pivots; and
  - at least one clamp assembly releasably contracting the lid into sealable engagement with the flange.
2. The sealable lid assembly as claimed in claim 1, further comprising a handle extending outwardly from the lid for assisting an operator in pivoting the lid.
3. The sealable lid assembly as claimed in claim 1, wherein two wheels are rotatably mounted to the lid and two spaced-apart tracks are disposed on the

vessel in positions to respectively engage the wheels, whereby binding of the lid is reduced as the lid pivots and moves vertically along the shaft.

4. The sealable lid assembly as claimed in claim 1, further comprising a gasket disposed within the channel releasably and sealably engaging the protrusion.

5. The sealable lid assembly as claimed in claim 4, wherein the gasket either comprises or is coated with a tetrafluoroethylene fluorocarbon polymer, a fluorinated ethylene-propylene resin, or a mixture thereof.

6. The sealable lid assembly as claimed in claim 1, wherein the at least one clamp assembly comprises:

a threaded bolt pivotally mounted to the vessel;

a wing nut having mating threads rotatably disposed on the bolt; and

5 a receiver mounted to the lid and having a U-shaped slot capable of receiving the bolt, whereby the lid is sealed by placing the bolt into the U-shaped slot and rotating the wing nut in one direction to exert pressure against the receiver and released by rotating the wing nut in the opposite direction and pivoting the bolt out of the U-shaped slot.

7. The sealable lid assembly as claimed in claim 1, wherein the at least one clamp assembly comprises:

a clamp pin mounted to the vessel and

a J-shaped clamp positioned on the lid to removably engage the claim pin,

5 whereby the lid is sealed by engaging the J-shaped clamp with the clamp pin and release by disengaging the J-shaped clamp from latch pin.

8. The sealable lid assembly as claimed in claim 1, wherein the lid comprises a substantially dome-shaped top and a substantially planar bottom, wherein the top and bottom in combination define a chamber.

9. The sealable lid assembly as claimed in claim 8, further comprising: insulation disposed within the cavity.

10. The sealable lid assembly as claimed in claim 8, wherein the protrusion extends from the bottom.

11. The sealable lid assembly as claimed in claim 1, wherein the at least one track has a rounded shoulder and an elongated ramp extending from the shoulder along an angle of about 30° to about 45° with respect to the distal end of the flange.

12. A sealable lid assembly for an opening of a vessel, comprising:  
a flange extending outwardly from the vessel to a distal end and surrounding the opening to define a manhole;

at least one wall extending from the flange proximate the distal end, the wall  
5 and the flange defining a channel for receiving a gasket;

a lid pivotally and telescopically mounted to the vessel capable of releasably and sealably engaging the gasket disposed within the channel;

at least one wheel rotatably mounted to the lid;

at least one elongated track extending outwardly from the vessel in a position  
10 to engage the at least one wheel and raise the lid vertically above the flange as the lid pivots; and

at least one clamp assembly releasably contracting the lid into sealable engagement with the flange.

13. The sealable lid assembly as claimed in claim 12, further comprising a handle extending outwardly from the lid for assisting an operator in raising and pivoting the lid.

14. The sealable lid assembly as claimed in claim 12, further comprising a gasket disposed within the channel releasably and sealably engaging the lid.

15. The sealable lid assembly as claimed in claim 12, wherein the at least one clamp assembly comprises:

a threaded bolt pivotally mounted to the vessel;

a wing nut having mating threads rotatably disposed on the bolt; and

5 a receiver mounted to the lid and having a U-shaped slot capable of receiving the bolt, whereby the lid is sealed by placing the bolt into the U-shaped slot and rotating the wing nut in one direction to exert pressure against the receiver and released by rotating the wing nut in the opposite direction and pivoting the bolt out of the U-shaped slot.

16. The sealable lid assembly as claimed in claim 12, wherein the at least one clamp assembly comprises:

a clamp pin mounted to the vessel and

a J-shaped clamp positioned on the lid to removably engage the claim pin,

5 whereby the lid is sealed by engaging the J-shaped clamp with the clamp pin and release by disengaging the J-shaped clamp from latch pin.

17. The sealable lid assembly as claimed in claim 12, wherein the lid comprises a substantially dome-shaped top and a substantially planar bottom, wherein the top and bottom in combination define a chamber.


18. The sealable lid assembly as claimed in claim 17, further comprising a protrusion extending from the bottom and insertable into the channel.

19. The sealable lid assembly as claimed in claim 17, further comprising insulation disposed within the cavity.


20. The sealable lid assembly as claimed in claim 12, wherein the at least one track has a rounded shoulder and an elongated ramp extending from the shoulder along an angle of about 30° to about 60° with respect to the distal end of the flange.

### ABSTRACT OF THE DISCLOSURE

A sealable lid assembly for a vacuum distillation apparatus has a lid pivotally and telescopically mounted to the vacuum distillation apparatus. Spaced-apart wheels are rotatably mounted to the lid. Tracks are disposed on the vacuum distillation apparatus in a position to engage the wheels and raise the lid vertically above a manhole of the vacuum distillation apparatus upon pivotal movement of the lid, which is initiated by nominal physical exertion of a single operator. Extending outwardly from and adjacent the manhole is a flange. The flange has a channel to receive a gasket. A protrusion extends outwardly from a bottom of the lid in a position to extend into the channel and sealably engage the gasket when the wheels disengage the tracks. Clamp assemblies are provided to releasably engage the lid with the flange and draw the protrusion into sealable, releasable engagement with the gasket. The gasket can be an endless type or non-endless type with obtuse faces oppositely and matingly positioned adjacent one another in the channel. A handle extends outwardly from the lid to assist the operator in pivotally moving the lid.




**Fig. 1**




**Fig. 3**












FIG 7

## DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As the below named inventors, we hereby declare that:

Our residence, post office addresses and citizenship are as stated below next to our names.

We believe we are the original, first and joint inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled: **SEALABLE LID FOR VACUUM DISTILLATION APPARATUS**

the specification of which

(check one) ☒ is attached hereto.

☐ was filed on \_\_\_\_\_ as Application Serial No. \_\_\_\_ / \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

We hereby state that we have reviewed and understand the contents of the above-identified specification, including the claims.

We acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

We hereby claim:

We hereby claim the benefit under Title 35, United States Code, §119 of any United States provisional parent application, foreign application(s) for patent or inventor's certificate listed below and have also identified below any United States provisional patent application, foreign application for patent or inventor's certificate having a filing date before that of the above-identified application on which priority is claimed:

Prior U.S. Provisional Application(s): **Provisional Application Serial Number 60/128,818, Filed April 12, 1999.**

We hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, we acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing of the prior application and the national or PCT international filing date of this application:

Prior Application(s): **None**

We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

As a named inventor, we hereby appoint the following attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Louis T. Isaf	Reg. No. 29,078
James F. Vaughan	Reg. No. 31,889
Steven D. Kerr	Reg. No. 32,472
D. Scott Sudderth	Reg. No. 34,026
Michael A. Cicero	Reg. No. 34,562
John T. Timar	Reg. No. 32,497
Li Wang	Reg. No. 44,393
Jeffery B. Arnold	Reg. No. 39,540
Judy C. Jarecki-Black	Reg. No. 44,170
Steven L. Schmid	Reg. No. 39,358

SEND CORRESPONDENCE TO:  
Jeffery B. Arnold  
Womble Carlyle Sandridge & Rice  
P. O. Box 725388  
Atlanta, Georgia 31139-9388

DIRECT PHONE CALLS TO:  
Jeffery B. Arnold  
(404) 872-7000

Inventor's Signature: \_\_\_\_\_

*Michael D. Mabry*

Full Name of Inventor: Michael D. Mabry

Date: \_\_\_\_\_


*04/07/00*

Citizenship: USA

Residence: 3172 Oak Springs Trace  
Marietta, GA 30066-3983

Post Office: 3172 Oak Springs Trace  
Marietta, GA 30066-3983

Inventor's Signature:



Full Name of Inventor: Donald R. McAllister

Date:

04/07/00

Citizenship: USA

Residence: 539 Cowart Mountain Trail  
Waleska, GA 30183

Post Office: 539 Cowart Mountain Trail  
Waleska, GA 30183